


# Wire Wound Chip Ceramic Inductor -MWSD-CP/CH Series

Operating Temp. : -40°C~+125°C



## FEATURES

- Small chip suitable for surface mounting
- High Q value and high self-resonant frequency with ceramic material
- Tight inductance tolerance and stable inductance at high frequency
- Lower DCR, higher Q and larger current than MWSD-C series
- Inductance of MWSD-CH series is larger than MWSD-CP series


## APPLICATIONS

- High frequency circuit in telecommunication and other equipments
- Mobile phones and other electronic devices
- Bluetooth, W-LAN, Broadband network

## PRODUCT IDENTIFICATION

<u>MWSD</u> ①	<u>1005</u> ②	<u>C</u> ③	<u>P</u> ④	<u>10N</u> ⑤	<u>J</u> ⑥	<u>S</u> ⑦	<u>T</u> ⑧	<u>F</u> ⑨																																																										
①	②	③	④	⑤	⑥	⑦	⑧	⑨																																																										
<table border="1"> <thead> <tr> <th colspan="2">Type</th> </tr> </thead> <tbody> <tr> <td>MWSD</td> <td>Wire Wound Chip Inductor</td> </tr> </tbody> </table>	Type		MWSD	Wire Wound Chip Inductor	<table border="1"> <thead> <tr> <th colspan="2">External Dimensions</th> </tr> </thead> <tbody> <tr> <td colspan="2">1005 [0402]</td> </tr> </tbody> </table>	External Dimensions		1005 [0402]		<table border="1"> <thead> <tr> <th colspan="2">Material Code</th> </tr> </thead> <tbody> <tr> <td>C</td> <td>Ceramic</td> </tr> </tbody> </table>	Material Code		C	Ceramic	<table border="1"> <thead> <tr> <th colspan="2">Feature Type</th> </tr> </thead> <tbody> <tr> <td>P</td> <td>Large Current &amp; High Q</td> </tr> <tr> <td>H</td> <td>Large Inductance &amp; Large Current &amp; High Q</td> </tr> </tbody> </table>	Feature Type		P	Large Current & High Q	H	Large Inductance & Large Current & High Q	<table border="1"> <thead> <tr> <th colspan="2">Nominal Inductance</th> </tr> </thead> <tbody> <tr> <th>Example</th> <th>Nominal Value</th> </tr> <tr> <td>10N</td> <td>10nH</td> </tr> <tr> <td>R10</td> <td>100nH</td> </tr> <tr> <td>1R0</td> <td>1.0μH</td> </tr> </tbody> </table>	Nominal Inductance		Example	Nominal Value	10N	10nH	R10	100nH	1R0	1.0μH	<table border="1"> <thead> <tr> <th colspan="2">Inductance Tolerance</th> </tr> </thead> <tbody> <tr> <td>B</td> <td>±0.1nH</td> </tr> <tr> <td>C</td> <td>±0.2nH</td> </tr> <tr> <td>S</td> <td>±0.3nH</td> </tr> <tr> <td>D</td> <td>±0.5nH</td> </tr> <tr> <td>G</td> <td>±2%</td> </tr> <tr> <td>H</td> <td>±3%</td> </tr> <tr> <td>J</td> <td>±5%</td> </tr> <tr> <td>K</td> <td>±10%</td> </tr> </tbody> </table>	Inductance Tolerance		B	±0.1nH	C	±0.2nH	S	±0.3nH	D	±0.5nH	G	±2%	H	±3%	J	±5%	K	±10%	<table border="1"> <thead> <tr> <th colspan="2">Feature Type</th> </tr> </thead> <tbody> <tr> <td>S</td> <td>Sn Plating Five-faces Coating</td> </tr> </tbody> </table>	Feature Type		S	Sn Plating Five-faces Coating	<table border="1"> <thead> <tr> <th colspan="2">Packing</th> </tr> </thead> <tbody> <tr> <td>T</td> <td>Tape &amp; Reel</td> </tr> </tbody> </table>	Packing		T	Tape & Reel	<table border="1"> <thead> <tr> <th colspan="2">Hazardous Substance Free Products</th> </tr> </thead> <tbody> <tr> <td colspan="2">F</td> </tr> </tbody> </table>	Hazardous Substance Free Products		F	
Type																																																																		
MWSD	Wire Wound Chip Inductor																																																																	
External Dimensions																																																																		
1005 [0402]																																																																		
Material Code																																																																		
C	Ceramic																																																																	
Feature Type																																																																		
P	Large Current & High Q																																																																	
H	Large Inductance & Large Current & High Q																																																																	
Nominal Inductance																																																																		
Example	Nominal Value																																																																	
10N	10nH																																																																	
R10	100nH																																																																	
1R0	1.0μH																																																																	
Inductance Tolerance																																																																		
B	±0.1nH																																																																	
C	±0.2nH																																																																	
S	±0.3nH																																																																	
D	±0.5nH																																																																	
G	±2%																																																																	
H	±3%																																																																	
J	±5%																																																																	
K	±10%																																																																	
Feature Type																																																																		
S	Sn Plating Five-faces Coating																																																																	
Packing																																																																		
T	Tape & Reel																																																																	
Hazardous Substance Free Products																																																																		
F																																																																		

## SHAPE AND DIMENSIONS



Unit: mm

Series	A	B	C	D	E	H Ref.	I Ref.	J Ref.
MWSD1005CP	1.10±0.1	0.6±0.1	0.6±0.1	0.5±0.1	0.2±0.1	0.65	0.35	0.50
MWSD1005CH	1.10±0.1	0.6±0.1	0.6±0.1	0.5±0.1	0.15±0.1	0.65	0.35	0.50

## SPECIFICATIONS

### MWSD1005CP TYPE

Part Number	Inductance	Tolerance	Min. Quality Factor	L/Q Test Freq.	Min. Self-resonant Frequency	Max. DC Resistance	Max. Rated Current
Units	nH	-	-	MHz	GHz	Ω	mA
Symbol	L	-	Q	Freq.	S.R.F	DCR	I <sub>r</sub>
MWSD1005CP1N0□T	1.0	C,S,D	20	250	16.0	0.030	2300
MWSD1005CP2N0□T	2.0	B,C,S,D,J,K	24	250	15.2	0.038	2100
MWSD1005CP2N2□T	2.2	C,S,D,J,K	25	250	15.1	0.038	2100
MWSD1005CP2N4□T	2.4	S,D	23	250	14.0	0.042	2000
MWSD1005CP2N7□T	2.7	C,S,D,J,K	24	250	13.0	0.056	1500
MWSD1005CP3N3□T	3.3	B,C,S,D,J,K	28	250	12.8	0.045	1700
MWSD1005CP3N6□T	3.6	C,S,D,J,K	28	250	11.7	0.045	1700
MWSD1005CP3N9□T	3.9	C,S,D,J,K	28	250	9.50	0.045	1700
MWSD1005CP4N3□T	4.3	B,S,D,J,K	27	250	7.15	0.050	1600
MWSD1005CP4N7□T	4.7	S,D,J,K	23	250	6.85	0.075	1500
MWSD1005CP5N1□T	5.1	B,S,D,J,K	20	250	6.80	0.100	1200
MWSD1005CP5N6□T	5.6	B,S,D,J,K	29	250	6.50	0.048	1600
MWSD1005CP6N2□T	6.2	B,S,D,J,K	29	250	5.80	0.050	1600
MWSD1005CP6N8□T	6.8	G,H,J,K	28	250	5.80	0.070	1500
MWSD1005CP7N5□T	7.5	G,H,J,K	26	250	5.40	0.080	1400
MWSD1005CP8N2□T	8.2	G,H,J,K	28	250	5.40	0.065	1500
MWSD1005CP8N7□T	8.7	G,H,J,K	29	250	5.00	0.070	1500
MWSD1005CP9N0□T	9.0	G,H,J,K	27	250	5.00	0.080	1400
MWSD1005CP9N5□T	9.5	G,H,J,K	28	250	4.70	0.075	1400
MWSD1005CP10N□T	10	G,H,J,K	26	250	4.70	0.085	1300
MWSD1005CP11N□T	11	G,H,J,K	29	250	4.70	0.070	1400
MWSD1005CP12N□T	12	G,H,J,K	28	250	4.40	0.100	1200
MWSD1005CP13N□T	13	G,H,J,K	27	250	4.20	0.140	870
MWSD1005CP15N□T	15	G,H,J,K	28	250	3.90	0.115	1100
MWSD1005CP16N□T	16	G,H,J,K	27	250	3.70	0.130	850
MWSD1005CP17N□T	17	G,H,J,K	26	250	3.70	0.230	650
MWSD1005CP18N□T	18	G,H,J,K	26	250	3.55	0.120	900
MWSD1005CP19N□T	19	G,H,J,K	26	250	3.50	0.145	850
MWSD1005CP20N□T	20	J,K	27	250	3.50	0.155	780

## SPECIFICATIONS

### MWSD1005CP TYPE

Part Number	Inductance	Tolerance	Min. Quality Factor	L/Q Test Freq.	Min. Self-resonant Frequency	Max. DC Resistance	Max. Rated Current
Units	nH	-	-	MHz	GHz	$\Omega$	mA
Symbol	L	-	Q	Freq.	S.R.F	DCR	I <sub>r</sub>
MWSD1005CP21N□T	21	G,H,J,K	25	250	1.70	0.460	450
MWSD1005CP22N□T	22	G,H,J,K	28	250	3.30	0.190	800
MWSD1005CP23N□T	23	G,H,J,K	28	250	3.30	0.160	800
MWSD1005CP24N□T	24	G,H,J,K	27	250	3.15	0.275	700
MWSD1005CP25N□T	25	G,H,J,K	26	250	3.15	0.260	700
MWSD1005CP26N□T	26	G,H,J,K	27	250	3.15	0.275	700
MWSD1005CP27N□T	27	G,H,J,K	27	250	3.20	0.330	450
MWSD1005CP30N□T	30	G,H,J,K	25	250	2.90	0.350	450
MWSD1005CP33N□T	33	G,H,J,K	28	250	2.80	0.330	490
MWSD1005CP36N□T	36	G,H,J,K	26	250	2.80	0.360	480
MWSD1005CP37N□T	37	G,H,J,K	26	250	2.70	0.480	470
MWSD1005CP39N□T	39	G,H,J,K	28	250	2.60	0.430	450
MWSD1005CP40N□T	40	G,H,J,K	28	250	2.60	0.520	450
MWSD1005CP43N□T	43	G,H,J,K	26	250	2.50	0.520	450
MWSD1005CP47N□T	47	G,H,J,K	28	250	2.40	0.580	420
MWSD1005CP51N□T	51	G,H,J,K	26	250	2.30	0.700	360

### MWSD1005CH TYPE


Part Number	Inductance	Tolerance	Min. Quality Factor	L/Q Test Freq.	Min. Self-resonant Frequency	Max. DC Resistance	Max. Rated Current
Units	nH	-	-	MHz	GHz	$\Omega$	mA
Symbol	L	-	Q	Freq.	S.R.F	DCR	I <sub>r</sub>
MWSD1005CH56N□T	56	G,H,J,K	31	250	2.07	0.900	330
MWSD1005CH68N□T	68	G,H,J,K	31	250	1.84	1.000	320
MWSD1005CH82N□T	82	G,H,J,K	31	250	1.75	1.100	315
MWSD1005CHR10□T	100	G,H,J,K	30	250	1.58	1.200	310
MWSD1005CHR12□T	120	G,H,J,K	29	250	1.25	1.200	310
MWSD1005CHR15□T	150	G,H,J,K	29	100/250	1.14	2.000	240
MWSD1005CHR16□T	160	G,H,J,K	29	100/250	1.65	2.400	240
MWSD1005CHR18□T	180	G,H,J,K	32	100/250	1.08	2.500	240
MWSD1005CHR22□T	220	G,H,J,K	32	100/250	0.96	3.500	160

※: Please refer to "Measurement Notice for RF Inductors".


# TYPICAL ELECTRICAL CHARACTERISTICS

## MWSD1005CP TYPE

Inductance vs. Frequency Characteristics




Q vs. Frequency Characteristics



## MWSD1005CH TYPE

Inductance vs. Frequency Characteristics



Q vs. Frequency Characteristics

