

ORDERING CODE

JV R 07 N 181 K 6 5 Y AW

Joyin ZnO Varistor
久尹氧化鋅壓敏電阻

R=RoHS
H=RoHS + Halogen free
+ Non Flammable

Element Size (disc dia.)
瓷片直徑別

05 = ϕ 5mm
07 = ϕ 7mm
10 = ϕ 10mm
14 = ϕ 14mm
20 = ϕ 20mm

Series 系列別

N=Standard 標準系列
S=High Surge 高突波電流系列
U=Ultra Surge 超高突波電流系列

Varistor Voltage 電壓值

The first two digits indicate voltage.
前兩位數字代表電壓

The third digit signifies the number of zeroes.
第三位數字代表電壓0的次數

for example 例如：

080=8V
180=18V
181=180V
182=1800V

Varistor Voltage Tolerance
壓敏電壓容許差

K = \pm 10%
L = \pm 15%
M = \pm 20%
P = \pm 25%

Lead Diameter
線徑

6 = 0.6 ± 0.05 mm
8 = 0.8 ± 0.05 mm
1 = 1.0 ± 0.05 mm

Lead Length & Packaging
腳長及包裝方式

50 = 5 ± 1.0 mm for Straight lead
5 \pm 0.5mm for Kink lead

U4 = 24mm min. for Bulk and Kink lead

U5 = 25mm min. for Bulk and Straight lead

AW= H0 16mm for Ammo and Kink lead

AY = H0 20mm for Ammo and Straight lead

RW= H0 16mm for T/R and Kink lead

RY = H0 20mm for T/R and Straight lead

* Special spec per request.

Lead Style 腳型

Y=Vertical Kink Lead (standard)

P=Straight Lead

* Special lead styles per request

Lead Spacing 線距

5=5.0mm

7=7.5mm

1=10mm