



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: 433.92 MHz 0.3MHzBW SMD 3.8x3.8 mm RF SAW Filter

(This part is compliant with AEC-Q200)

TST Parts No.:TA1884A

Customer Parts No.: _____

Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Kazuma Lee *Kazuma Lee*

Approval by: _____ Andy Yu *Andy Yu*

Date: _____ 07 / 09 / 2018

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 433.92 MHz

MODEL NO.:TA1884A

REV. NO.: 2.0

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 6V
3. Operating Temperature: -40°C to +95°C
4. Storage Temperature: -40°C to +95°C
5. AEC-Q200
6. Moisture Sensitivity Level: Level 1(MSL1)

RoHS Compliant
Lead free
Lead-free soldering

Electrostatic Sensitive Device



B. ELECTRICAL CHARACTERISTICS:

Item	Unit	Min.	Typ.	Max.
Center frequency Fc	MHz	-	433.92	-
3dB BW	MHz	-	0.63	-
Minimum insertion loss IL(min)				
Incl. loss of matching elements(Q=) *1)	dB	-	2.7	3.4
Exclude loss in matching elements *2)	dB	-	2.5	3.2
Passband (relative to IL_{min}) *1)				
433.76 ~ 434.08 MHz	dB	-	0.5	2.0
433.74 ~ 434.10 MHz	dB	-	0.7	3.0
433.70 ~ 434.14 MHz	dB	-	1.2	6.0
Attenuation (relative to IL_{min}) *1)				
10.000 ~ 414.00 MHz	dB	38	43	-
414.00 ~ 423.50 MHz	dB	38	43	-
423.50 ~ 431.72 MHz	dB	29	34	-
431.72 ~ 432.12 MHz	dB	26	36	-
432.12 ~ 433.10 MHz	dB	10	24	-
434.70 ~ 434.92 MHz	dB	10	17	-
434.92 ~ 442.00 MHz	dB	13	21	-
442.00 ~ 500.00 MHz	dB	40	44	-
500.00 ~ 700.00 MHz	dB	50	54	-
700.00 ~ 805.00 MHz	dB	45	55	-
805.00 ~ 1000.00 MHz	dB	60	70	-
Impedance at Fc, Input *1) Zin = Rin//Cin Zs	Ω//pF	184.5Ω//3.6 pF		
Impedance at Fc, Output *1) Zout = Rout//Cout ZL	Ω//pF	184.5Ω//3.6 pF		


*1) : The matching circuit is real by actual passive components.
0805 Coilcraft CS series chip conductor is used for inductor.
0402 muRata GRM series is used for capacitor.

*2) : The matching circuit is ideal by simulation.

C. FREQUENCY CHARACTERISTICS:




Smith Chart




D. MEASUREMENT CIRCUIT:

The matching circuit is real by actual passive components.



E.OUTLINE DRAWING:



A: Input Ground or Input
B: Input or Input Ground
E: Output Ground or Output
F: Output or Output Ground
C,D,G,H : Ground
 △ : Year Code
 □ : Date Code
 Unit : mm


△ : Year Code

Year	2015	2016
	2017	2018
	2019	2020
Product Code	A	a

□ : Date Code table

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z


F. PCB FOOTPRINT:




G. PACKING:

1. REEL DIMENSION

(Please refer to FR-75D10 for packing quantity)



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE:

1. Preheating shall be fixed at $150 \sim 180^\circ\text{C}$ for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at $245 \sim 260^\circ\text{C}$ peak (min. 10sec).
4. Time : 2 times.

